




PRODUCT DESCRIPTION

- » Slotted and ground
- » Metallically sealed for tools with internal coolant supply
- » Suitable for HWZ 1155, HWZ 2255, HWZ 1161, HWZ 2261, HWZ 11651, HWZ 22651, HWZ 1166 and HWZ 2266

APPLICATION

- » For reduction of the clamping diameter
- » For drilling, reaming, milling and tool sharpening



d2	l	l1	l2	d	d1	No.	EUR
16	40	44	29	12	4	HWZ 9060/12/ 4	<>
16	40	44	36	12	6	HWZ 9060/12/ 6	<>
16	40	44	37	12	8	HWZ 9060/12/ 8	<>
25	50	54	28	20	3	HWZ 9060/20/ 3	<>
25	50	54	28	20	4	HWZ 9060/20/ 4	<>
25	50	54	28	20	5	HWZ 9060/20/ 5	<>
25	50	54	36	20	6	HWZ 9060/20/ 6	<>
25	50	54	37	20	8	HWZ 9060/20/ 8	<>
25	50	54	40	20	10	HWZ 9060/20/10	<>
25	50	54	45	20	12	HWZ 9060/20/12	<>
25	50	54	48	20	16	HWZ 9060/20/16	<>

i Caution! Never clamp without tool. This will damage the reduction sleeve!